

SPECIFICATIONS
MODELS 4110C SINGLE CHANNEL & 4114B 4-CHANNEL LIVM
LINE-POWERED CURRENT SOURCE POWER UNITS

SPECIFICATIONS	VALUE	UNITS
SENSOR DRIVE CURRENT ADJUSTMENT RANGE	2 to 20	mA
COMPLIANCE (SUPPLY) VOLTAGE	+24	VDC
VOLTAGE GAIN	1	UNITY
DE-COUPLING CAPACITOR	10	µF
PULLDOWN RESISTOR	1	MEGOHM
COUPLING TIME CONSTANT, NO LOAD	10	SECONDS
W/1 MEGOHM LOAD	1	SECONDS
LOWER -3db FREQUENCY, NO LOAD	.016	Hz
W/1 MEGOHM LOAD	.03	Hz
HIGH FREQUENCY RESPONSE:	DETERMINED BY SENSOR, CABLE LENGTH AND SENSOR DRIVE CURRENT.	
BACKGROUND ELECTRICAL NOISE, WIDEBAND	150	µV RMS
SENSOR CONNECTOR, REAR PANEL, MODEL 4110C	BNC	JACK
MODEL 4114B	10-32 (4)	JACK
OUTPUT CONNECTOR, REAR PANEL, ALL MODELS	BNC	JACK
POWER CORD, 3-WIRE W/GND	6	FT
POWER REQUIRED: [1]		
MODEL 4110C	1.1	VA
MODEL 4114	4.4	VA
SIZE, H x W x D [2]	BOTH MODELS	5.5 x 1.6 x 8.0
WEIGHT	BOTH MODELS	32/907
		OZ/GRAMS

[1] 115 VAC, 50-60 Hz FOR STANDARD MODELS. EXPORT ["E"] VERSIONS REQUIRE 230 VAC, 50-60Hz.

[2] RACK MOUNTING: UP TO 10 UNITS MAY BE MOUNTED IN 19 IN. WIDE MODEL 4200 RACK ADAPTOR. UNIT IS SECURED IN RACK BY MEANS OF A CAPTIVATED 10-32 THUMB SCREW AT THE BOTTOM OF THE FRONT PANEL.