

CLSx - Steering Effort Sensor



The innovative steering effort sensor CLS^x sets new standards in size of the housing as well as in resolution and accuracy of measurement values. The sensor is placed between steering column and original steering wheel of the vehicle, preserving all steering wheel functions.

The CLS^x captures precisely the parameters torque, steering angle and rotational velocity. Optionally, it also acquires acceleration in the center of the steering column (x, y and z direction) as well as rotational acceleration.

Measurement data are digitized for a highly fail-safe data transfer, with a resolution of 16 bits (internally: 24 bits). Together with its innovative, ultra slim sensor body design, this leads to an unprecedented precision of

torque measurement of 0.1% FS.

Highlights

- Ultra slim sensor body design for seamless integration with minimal extension of steering column
- All functions of the steering wheel are preserved
- Steering torque range ± 100 Nm
- Measuring angle range $\pm 1440^\circ$
- Rotational velocity range $\pm 1000^\circ/\text{sec}$
- Acceleration in x, y, z direction
- Rotational acceleration

For data output and parametrization, the receiver and control unit offers both analog and digital interfaces (CAN, Ethernet). At the 2.83" Farbdisplay (320 x 240 px) integrated in the control unit, all measurement values are displayed in physical dimensions.

Overview of the available variants

Order Code	article number
H-SEN-CMX-CLSx100-ACC CLS ^x Steering Effort Sensor 100 Nm with acceleration sensor	1380006

Included accessories

Transportation case,
 Calibration certificate with test equipment,
 Remote control for autozero including remote cable,
 Ethernet cable,
 Receive unit,
 SD card ≥ 2 GB,
 Power adaptor,
 8 screws for each: steering wheel adaptor and the steering column adaptor,
 Steering wheel puller,
 CD with manual,
 Mounting unit for the angle encoder bracket to a fix zero position.



Optional accessories

- H-SEN-CMX-CLS-REF Reference Mark for zero position 1380003
 CLS^x Option Reference Mark for permanent storage of
 the zero position
 Only available with new order, no refit possible
- H-ZUB-CMX-CLS-ADP-LR-R Steering wheel adaptor for CLS^x; blank without specific 1380008
 toothing; for manufacturing the specific toothing by
 yourself
- H-ZUB-CMX-CLS-ADP-LR-ST Steering wheel adaptor for CLS^x; with matched 1380016
 toothing for known vehicles, only possible after
 confirmation of an existing adaptor for the car
- H-ZUB-CMX-CLS-ADP-LR-SP Steering wheel adaptor for CLS^x; with new adaption 1380004
 for a matched toothing; technical specification of your
 steering wheel (drawings, example etc.) is to be
 provided by the customer for the development
- H-ZUB-CMX-CLS-ESP ESP Upgrade for steering wheel adaptor 1380009
- H-ZUB-CMX-CLS-ADP-LS-R Steering column adaptor for CLS^x; blank without 1380010
 special toothing; for manufacturing the special
 toothing by yourself
- H-ZUB-CMX-CLS-ADP-LS-ST Steering column adaptor for CLS^x; with matched 1380011
 toothing for known vehicles, only possible after
 confirmation of an existing adaptor for the car
- H-ZUB-CMX-CLS-ADP-LS-SP Steering column adaptor for CLS^x; with new adaption 1380005
 for a matched toothing; technical specification of your
 steering column (drawings, example etc.) is to be
 provided by the customer for the development
- H-ZUB-CMX-CLS-Momo Momo steering wheel incl. adaptor to CLS^x 1380012
 Only possible after confirmation of an existing adaptor for the car.



Further components

- H-TEL-CMX-DX-FRAME Mounting frame for one receiver unit 1350239
 Mounting frame for one receiver unit.
 Optionally with protection cap for thumbwheel.



Technical Specs - CLSx

Steering Torque		
Parameter	Value	Remarks
Measuring principle	temperature compensated strain gauge application	
Measurement range	±100 Nm	
Accuracy	0.1% FS	
Bandwidth	0 to 800 Hz	sampling rate 5 kHz

Steering Angle		
Parameter	Value	Remarks
Measuring principle	incremental angle encoder	
Measurement range	±1440 °	
Accuracy	0.045 °	
Bandwidth	0 to 800 Hz	sampling rate 5 kHz

Rotational velocity		
Parameter	Value	Remarks
Measuring principle	Calculated from angle	
Measurement range	CAN: ±1000 °/s	
Bandwidth	0 to 800 Hz	sampling rate 5 kHz

Acceleration		
Acceleration x, y and z	in the center of the steering column, measurement range up to 5 g in x, y and z direction	
Rotational acceleration	measurement range ±10000 °/sec ²	

General Data		
Parameter	Value	Remarks
Sensor height	approx. 30 mm	w/o adaptors
Sensor weight	approx. 0.6 kg	w/o adaptors
Overload	>100% of the measurement range	
Mech. breaking torque	>500 Nm	
Adaption	special adaption sets for any car or truck manufacturer available	
Moment of inertia sensor	approx. 3000 g cm ²	
steering wheel or column adaptor	typ. approx. 500 g cm ²	
Working temperature	-20°C to +80°C	

Control Unit		
Power supply	9 to 36 V DC	
CAN-Output	freely configurable	
Analog output	freely configurable, output range max. ±10 V	
Auto zero	with push-button for torque and angle at the panel or by remote control	