

# Kestrel 4200 Plus

## Digital Realtime Motion Capture System



### CAMERA

<b>Frame Size (pixels)</b>	4.2 Megapixels
<b>Resolution</b>	2048 x 2048
<b>Frame Rate at Full Resolution</b>	200 fps
<b>Sensor Maximum Frame Rate</b>	10,000 fps
<b>Sensor Type</b>	Global Shutter
<b>Camera Power Supply</b>	HCP-8
<b>Camera Lens</b>	12-36mmVarifocal (standard) or Super-wide (option available)
<b>Camera Connectors</b>	Ethernet, Sync in/out
<b>Camera Cabling</b>	Standard Cat5E, Power over Ethernet
<b>Camera Body Dimensions</b>	4.75"D x 3.62"T x 3.62" W / 12.1cmD x 9.2cmT X 9.2cmW
<b>Camera Weight (including ringlight)</b>	1.98lbs / 0.90kg
<b>Number of Camera Mount Points</b>	Five (5)

### RINGLIGHT

<b>Strobe Type</b>	Near Infrared (750 nm), Full Infrared (850 nm)
<b>Strobe Electronics</b>	Integrated , Software Reprogrammable
<b>LEDs</b>	36 Surface Mount
<b>Adjustable Illumination</b>	Yes






## ENVIRONMENTAL

**Temperature, Operating** 10° to 25°C  
50° to 77°F

**Temperature, Storage** -40° to 65°C  
-40° to 149°F

**Relative Humidity** 20% to 80%  
(non-condensing)



## SYSTEM CONNECTIVITY

**Plug and Play Compatibility** Yes

**System Connectivity** Gigabit Ethernet

**Custom Control Interface** Yes

**Camera Number Indicator** Yes

**Integrated Camera Display Panel** No

**Insight Auto-Focus** Yes

**Communication Status Indicators** Yes

**Maximum Number of Cameras** Unlimited

**Multiple Camera Types in System** Yes

**Genlock to External Video Source** Yes

**Synchronize to External Signal** Yes

**IP Addressable** Yes

**IP Reconfigurable** Yes

**External A/D Sync and Clock** Yes

## Motion Analysis Corporation

707-579-6500

sales@motionanalysis.com

www.motionanalysis.com

6085 State Farm Drive, Suite 100  
Rohnert Park, CA 94928



Presented by: Absolute Gauge Technologies  
sales@absolute-gauge.com; www.absolute-gauge.com,  
Toronto: 416 754 3168, Montreal: 514 695 5147, Toll Free: 1 888 754 7008