



MOUNTING HOLE PREPARATION

PREPARE FLAT MOUNTING SURFACE OVER .50 MIN. DIA., (FLAT TO .001 TIR) BY MILLING, SPOTFACING, TURNING, ETC. AT CENTER, DRILL #21 (.159) DIA X .200 DEEP (MIN.). TAP 10-32 UNF-2B X .150 MIN. DEPTH. CLEAN SURFACES THOROUGHLY TO REMOVE CHIPS AND CUTTING OILS.

1. CASE MATERIAL: 316L STAINLESS STEEL. UNIT IS NON-MAGNETIC.
2. SEAL: HERMETIC
3. MOUNTING TORQUE ON 1/5" HEX: 20-25 LB-INCHES.
4. WEIGHT-25 GRAMS

REDRAWN ON CAD 5/10/95

EXCEPT AS OTHERWISE NOTED

ALL DIMENSIONS IN INCHES
TOLERANCE: .XXX = ± .XX = ±

SURFACE FINISH EXCEPT AS NOTED

BREAK EDGES TO DEBURR RADIUS OR CHAMFER

THESE DIAS TO T.I.R.

FILLETS - MAX RAD.



CHATSWORTH, CA.

SCALE	4X	REV	A	DATE	9-22-93	ECN	-
DATE	10/31/95		PART NO.	MODEL 3122C & C2			
DRAWN	N.C.	CHECKED	N.C.		MAT'L		
APPROVED		NEXT ASSEMBLY		USED ON			
TITLE						DWG NO.	
OUTLINE/INSTALLATION DRAWING						127-3122C	
MODEL 3122C & C2						SHEET 1 OF 1	

SPECIFICATIONS

MODELS 3122C/C2 CHARGE MODE ACCELEROMETERS

SPECIFICATION	VALUE	UNITS
RANGE	+/- 500	G
MAXIMUM SHOCK	2000	G, PEAK
MAXIMUM VIBRATION	1000	G, RMS
SENSITIVITY, +20%/-10%	(3122C) [1]	pC/G
	(3122C2) [1]	pC/G
MOUNTED RESONANT FREQUENCY, NOM.	25	KHz
FREQUENCY RESPONSE, +/- 5% [2]	[2] to 5000	Hz
OPERATING TEMPERATURE RANGE	(3122C)	F
	(3122C2)	F
CAPACITANCE, NOM.	(3122C)	pF
	(3122C2)	pF
AMPLITUDE LINEARITY	+/-2	%FS
TRANSVERSE SENSITIVITY	5	%
SIGNAL POLARITY [3]	NEGATIVE [2]	
SIZE, HEX x HEIGHT	0.5 X 0.96	IN
WEIGHT	25	GM
GROUND RETURN	CASE IS SIGNAL RETURN	
CONNECTOR, TRANSVERSE MOUNTED	COAXIAL	10-32
CASE MATERIAL	STAINLESS STEEL	316L
MOUNTING PROVISION	TAPPED HOLE IN BASE	10-32
ENVIRONMENTAL SEAL	HERMETIC, WELDED/GLASS-TO-METAL	

ACCESSORIES SUPPLIED (1) MODEL 6200 MOUNTING STUD

[1] Measured at 100Hz, 1G RMS. Calibration certificate supplied with each instrument traceable to NIST.

[2] Low frequency response is controlled by the charge amplifier discharge time constant and other factors.

[3] With acceleration into the base toward the top of the instrument.